



MTXL

- Tread of latest generation with massive tread blocks and maximum protection
- The optimal solution for toughest wheel loader applications without compromising on mileage and operating costs

04/2022

Dimension	Tread Depth	TRA Code	Ply Rating	Standard Rim	Outer Diameter	Width	TT/TL
23.5R25	49,0 mm	E4, L4	* / **	19.50/2.5	1650 mm	637 mm	TL
23.5R25	80,0 mm	L5	**	19.50/2.5	1650 mm	637 mm	TL
26.5R25	53,0 mm	E4, L4	* / **	22.00/3.0	1780 mm	699 mm	TL
26.5R25	80,0 mm	L5	**	22.00/3.0	1780 mm	718 mm	TL
29.5R25	58,0 mm	E4, L4	* / **	25.00/3.5	1910 mm	804 mm	TL
29.5R25	92,0 mm	L5	**	25.00/3.5	1910 mm	804 mm	TL
775/65R29	53,0 mm	E4, L4	* / **	24.00/3.0	1780 mm	792 mm	TL
35/65R33	61,0 mm	L4	** / ***	28.00/3.5	2050 mm	921 mm	TL
35/65R33	90,0 mm	L5	** / ***	28.00/3.5	2051 mm	921 mm	TL

APPLICATIONS

