



MINE D2

- Non-directional pattern, with tread and sidewall particularly protected
- Special compound for maximum cut and impact resistance as well as optimal cost per hour
- The continuous bridge in the middle guarantees a maximum footprint
- The large cross cuts extending over the shoulder ensure optimum traction
- Especially recommended for demanding applications, in conditions requiring maximum protection

06/2024

Dimension	Tread Depth	TRA Code	Ply Rating	Standard Rim	Outer Diameter	Width	TT/TL
15.5R25	60,0 mm	L5	*	12.00/1.3	1315 mm	418 mm	TL
17.5R25	62,0 mm	L5	* / **	14.00/1.5	1385 mm	475 mm	TL
20.5R25	72,0 mm	L5	* / **	17.00/2.0	1535 mm	562 mm	TL
23.5R25	80,0 mm	L5	* / **	19.50/2.5	1650 mm	637 mm	TL
26.5R25	80,0 mm	L5	* / **	22.00/3.0	1780 mm	718 mm	TL
29.5R25	92,0 mm	L5	* / **	25.00/3.5	1910 mm	804 mm	TL
35/65R33	90,0 mm	L5	* / **	28.00/3.5	2050 mm	921 mm	TL
45/65R39	100,0 mm	L5	*	36.00/4.5	2580 mm	1099 mm	TL
45/65R45	100,0 mm	L5	* / **	36.00/4.5	2697 mm	1159 mm	TL

APPLICATIONS

